FICHA TÉCNICA

626040NWK

LED LIGHT FRAME 40W 60X60CM 4000K WITH EMERGENCY KIT

LED LIGHT FRAME 60x60cm with emergency kit. 40W power and luminous flux of 3920lm. 120° symmetrical optical beam angle and 4000K color temperature. IP20 protection rating against external elements. Made of white finish aluminum and opal finish polycarbonate diffuser.

PRODUCT SPECIFICATIONS

Item code:	626040NWK
Description:	LED Light frame
EAN13 code:	8436548449414

ELECTRICAL DATA

Power:	40w
Voltage:	200-265vac
Frequency:	50-60Hz
ENEC Certification:	YES
Power factor:	0,9
Dimmable:	NOT
Electrical insulation class:	CLASS II
Connection:	L/N

LUMINOUS DATA

Color temperature:	4000K
Luminous efficiency:	98 lm/w
Lumens:	3920lm
LED chip model:	SMD 4014
Beam angle:	120°
Luminous distribution:	Symmetrical
Color rendering index:	>80
Color rendering index, minimum:	80
Color rendering index, maximum:	83
Standard desviation of colour matching:	<6
Luminous flux maintenance:	L90B10
Flicker index:	≤1,0

SVM (Stroboscopic Visibility Measure):	**≤0,4**
Flicker free:	**SIM**

TECHNICAL DATA

Protection rating:	**IP20 (Equipment protected against objects >12mm in diameter)**
Operating temperature:	**-20°~50°**
Mounting type:	**Recessed**

EMERGENCY KIT DATA

Power:	**4W**
Luminance:	**400lm**
Autonomy:	**90 minutes**
Function:	**Non-permanent**
Battery:	**Li-on 3.7v 2500mAh**

AVERAGE LIFESPAN

Working hours:	**45000 hrs**
Switching cycles:	**35000 ON/OFF**

PHYSICAL DATA

Housing

Material:	**Aluminum**
Finish:	**White**

Diffuser

Material:	**Polycarbonate**
Finish:	**Opal**

Weight

Weight:	**0,40 kg**

ENERGY EFFICIENCY 2023(UE-2019/2015) F

DIMENSIONS



LUMINOUS INTENSITY DISTRIBUTION CURVE





CERTIFICATIONS

CE & ROHS

EMC directive 2014/30/EU ELECTROMAGNETIC COMPATIBILIT

EN IEC 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment.
EN IEC 61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current =16 A per phase).
EN 61000-3-3	Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current <= 16 A per phase and not subject to conditional connection.
EN 61547	Equipment for general lighting purposes - EMC immunity requirements.

LVD directive 2014/35/EU LOW VOLTAGE

EN 60598-1	Luminaires - Part 1: General requirements and tests.
EN 60598-2-2	Luminaires - Part 2-2: Particular requirements - Recessed luminaires
EN IEC 62031	LED modules for general lighting - Safety specifications
EN 62493	Assessment of lighting equipment related to human exposure to electromagnetic Field

RoHS Directive 2011/65/EU and Delegated Directive (EU) 2015/863
Determination of Certain Substances in Electrotechnical Products.

IEC 62321-1	**IEC62321-2**
IEC 62321-3-1	**IEC 62321-5**
IEC 62321-4	**IEC 62321-6**
IEC 62321-7-1	**IEC 62321-7-2**
IEC 62321-8	

CE RoHS