

9624001212NW

UFO PLUS LED HIGH BAY LIGHT 240W 4000K 120°

UFO Plus LED industrial high bay light, 240W power and 34320lm luminous flux. Equipped with 320 pcs Lumileds LED chips and driver with 4kV surge protection. Symmetrical 120° beam angle and 4000K colour temperature. Protection rating IP65 and mechanical impact resistance rating IK08. Black aluminium body and transparent polycarbonate diffuser.



PRODUCT SPECIFICATIONS

Item code:	9624001212NW
Description:	LED industrial high bay light
EAN13 code:	8436568445120

ELECTRICAL DATA

Power:	240w
Voltage:	85-265vac
Frequency:	50-60Hz
Power factor:	0,9
Dimmable:	NOT
Driver Protection:	OVP, SCP, OPP, OTP
Overvoltage protection:	4kv
Electrical insulation class:	CLASS I
Connection:	L/N+TT

LUMINOUS DATA

Color temperature:	4000K
Luminous efficiency:	143lm/w
Lumens:	34320lm
LED chip brand:	Lumileds
LED chip model:	Luxeon 3030 2d
Number of LED chips:	320pcs
Beam angle:	120°
Luminous distribution:	Symmetrical
Color rendering index:	>80
Color rendering index, minimum:	80
Color rendering index, maximum:	85
Standard desviation of colour matching:	<6

Luminous flux maintenance:	L90B10
Flicker index:	≤1,0
SVM (Stroboscopic Visibility Measure):	≤0,4
Flicker free:	YES

TECHNICAL DATA

Protection rating:	IP65 (Dust-tight and protected against water jets)
Impact rating:	IK08 (5J)
Operating temperature:	-20°~50°
Mounting type:	Surface

AVERAGE LIFESPAN


Working hours:	45000 hrs
Switching cycles:	35000 ON/OFF

PHYSICAL DATA



Housing	
Material:	Aluminum
Finish:	Black
Diffuser	
Material:	Polycarbonate
Finish:	Transparent
Weight	
Weight:	3,30 kg

ENERGY EFFICIENCY 2023(UE-2019/2015)	D
--------------------------------------	---

DIMENSIONS



LUMINOUS INTENSITY DISTRIBUTION CURVE



CERTIFICATIONS

CE & ROHS

EMC directive 2014/30/EU ELECTROMAGNETIC COMPATIBILITY

- EN IEC 55015** Limits and methods of measurement of radio-frequency disturbance characteristics of lighting equipment and similar apparatus.
- EN 61547** Lighting equipment for general use. EMC immunity requirements.
- EN IEC 61000-3-2** Electromagnetic compatibility (EMC). Part 3-2: Limits. Limits for harmonic current emissions (equipment with input current ≤ 16 A per phase).
- EN 61000-3-3** Electromagnetic compatibility (EMC). Part 3-3: Limits. Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems for equipment with rated current ≤ 16 A per phase and not subject to conditional connection.

LVD directive 2014/35/EU LOW VOLTAGE

- EN 60598-1** Luminaires - Part 1: General requirements and tests.
- EN 60598-2-1** Luminaires - Part 2-1: Particular requirements - Fixed general purpose luminaires.

RoHS Directive 2011/65/EU and Delegated Directive (EU) 2015/863 Determination of Certain Substances in Electrotechnical Products.

- IEC 62321-4** **IEC 62321-5**
- IIEC 62321-7** **IEC 62321-6**
- IEC 62321-8**

