


711003010PCR

GADIR STREET LUMINAIRE DIMMABLE 100W PC AMBER 100°X130°

Gadir dimmable Street Luminaire for public lighting, 100W power and 13000lm luminous flux. Equipped with 192 pcs Lumileds SMD2835 LED chips and MOSO X6 dimmable driver. Asymmetrical 100° × 130° beam angle and PC Amber colour temperature. Protection rating IP66 and mechanical impact resistance rating IK08 vandal-resistant. Die-cast aluminium body with RAL 9007 grey finish. Polycarbonate lenses. Adjustable mounting arm for installation on poles or columns.



PRODUCT SPECIFICATIONS

Item code:	711003010PCR
Description:	Street luminaire for public lighting Gadir
EAN13 code:	8435724904952

ELECTRICAL DATA

Power:	100w
Voltage:	90-305vac
Frequency:	50/60 Hz
Power factor:	0,9
Dimmable:	YES
Driver model:	MOSO
Dimming:	0-10vac, PWM, DIM TO OFF
Control method:	Offline Programming
Timer:	YES
Driver protections:	OVP, SCP, OPP, OTP
Overvoltage protection:	6kv
Surge protection option:	10kv
Electrical insulation class:	CLASS I
Connection:	L/N+TT

LUMINOUS DATA

Color temperature:	PC Amber
Luminous efficiency:	130 lm/w
Lumens:	13000lm
LED chip brand:	Lumileds
LED chip model:	SMD 2835
Number of LED chips:	192 pcs

Beam angle:	100°x130°
Light distribution:	Asymmetric
Color rendering index:	>80
Luminous maintenance factor:	L95B10

TECHNICAL DATA

Protection rating:	IP66 (Dust-tight and protected against powerful water jets)
Impact rating:	IK08 (5J vandal-resistant)
Operating temperature:	-20°~50°
Mounting type:	Surface
Mounting method:	Vertical position support for column mounting Horizontal position support for pole mounting
Mounting device:	Inner diameter D62 mm
Tilt angle:	15°

AVERAGE LIFESPAN


Lifetime hours:	60000 hrs
Switching cycles:	40000 ON/OFF

PHYSICAL DATA

Luminaire body	
Material:	Die-cast aluminum
Finish:	Grey - RAL 9007
Lenses	
Material:	Polycarbonate
Finish:	Transparent
Weight	
Weight:	3,80 kg

ENERGY EFFICIENCY 2023 (EU-2019/2015) D

DIMENSIONS



EMC directive 2014/30/EU ELECTROMAGNETIC COMPATIBILIT

- EN IEC 55015** Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment.
- EN 61547** Equipment for general lighting purposes - EMC immunity requirements.
- EN IEC 61000-3-2** Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current =16 A per phase).
- EN 61000-3-3** Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection.

LVD directive 2014/35/EU LOW VOLTAGE

- EN IEC60598-1** Luminaires - Part 1: General requirements and tests.
- EN 60598-2-5** Luminaires - Part 2-5: Particular requirements - Floodlights.

RoHS Directive 2011/65/EU and Delegated Directive (EU) 2015/863

Determination of Certain Substances in Electrotechnical Products.

IEC 62321-4

IEC 62321-5

IEC 62321-6

IEC 62321-7-2

IEC 62321-8

