


TECHNICAL DATA



734070AM

URBAN VILLA LUMINAIRE 40W 2200K 70°X140°

Villa Street Luminaire for public lighting. 40W power and 4960lm luminous flux. Equipped with 64 pcs Lumileds SMD2835 LED chips and MOSSO driver. Asymmetrical 70° × 140° beam angle and 2200K colour temperature. Protection rating IP66 and mechanical impact resistance rating IK08. Die-cast aluminium housing with black finish, high-temperature epoxy coating. Polycarbonate lenses.



PRODUCT SPECIFICATIONS

Item code:	734070AM
Description:	Villa Street Luminaire for public lighting.

ELECTRICAL DATA

Power:	40w
Voltage:	90-305vac
Frequency:	50/60 Hz
Driver brand:	MOSSO
Driver model:	Serie X6
Driver ENEC certified:	YES
Power factor:	0,9
Dimmable:	NOT
Driver protections:	OVP, SCP, OPP, OTP
Overvoltage protection:	6kv
Surge protection option:	10kv
Electrical insulation class:	Class I
Connection:	L/N+TT

LUMINOUS DATA

Color temperature:	2200K
Luminous efficiency:	124 lm/w
Lumens:	4960lm
LED chip brand:	Lumileds
LED chip model:	SMD 2835
N.º of LED chip:	64 pcs
Beam angle:	70°x140°
Light distribution:	Asymmetric

Color rendering index:	>80
Luminous flux maintenance:	L95B10

TECHNICAL DATA

Protection rating:	IP66 (dust-tight equipment and protected against powerful water jets)
Impact rating:	IK08
Operating temperature:	-20°~50°
Mounting type:	Surface
Mounting method:	Mounting on arm or pole
Mounting accessory:	For installation on a column, the use of the specific pole mounting bracket (Ref. 74SOPORTE1) is required, not included with the luminaire.

AVERAGE LIFESPAN


Lifetime hours:	60000 hrs
Switching cycles:	40000 ON/OFF

PHYSICAL DATA



Housing	
Material:	Die-cast aluminium
Finish:	Black - high-temperature epoxy paint
Diffuser	
Material:	Polycarbonate
Finish:	Transparent
Weight	
Weight:	11,50 kg

ENERGY EFFICIENCY 2023(UE-2019/2015)	D
---	----------

DIMENSIONS



CURVA DE DISTRIBUCIÓN DE INTENSIDAD LUMINOSA



CERTIFICATIONS

CE & ROHS

EMC directive 2014/30/EU ELECTROMAGNETIC COMPATIBILIT

- EN IEC 55015** Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment.
- EN IEC 61000-3-2** Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current =16 A per phase).
- EN 61000-3-3** Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection.
- EN 61547** Equipment for general lighting purposes - EMC immunity requirements.

LVD directive 2014/35/EU LOW VOLTAGE

- EN IEC60598-1** Luminaires - Part 1: General requirements and tests.
- EN IEC 60598-2-1** Luminaires - Part 2-1: Particular requirements - Fixed general purpose luminaires.

RoHS Directive 2011/65/EU and Delegated Directive (EU) 2015/863

Determination of Certain Substances in Electrotechnical Products.

IEC 62321-4

IEC 62321-5

IEC 62321-6

IEC 62321-7-2

IEC 62321-8

